

Audio In DVI, Digital Computer S-Video Composite Video

Small, quiet, and portable. Easy to use for traveling!



ImagePro 8746 Miniature Portable DLP projector

- Ultra Light, 2.4 lbs.
- XGA resolution
- 1100 lumens brightness
- Small, quiet
- Extremely easy to use

Two year warranty



8746 DUKANE

ImagePro 8746 **Ultra portable DLP projector**

A way to present your images anywhere

The Dukane ImagePro 8746 provides exceptional performance with tremendous portability. It's the ideal way to present rich, saturated color images from your PC or video source.

The projector is one-half the size of most laptop computers while providing a full set of features. Use it as your traveling companion or just as a fast way to collaborate with your associates.

Key features:

- Ultra light weight
- 1100 lumens brightness
- Crisp XGA resolution, with auto sizing image
- •DVI connection for analog and digital images
- •Full-function remote control with USB mouse operation
- •Computer plus composite, and S-video inputs
- Only 2.4 lbs. in a miniature package
- 1.3X zoom lens for flexible projector placement
- Audio sound from built-in speaker

Projection throw distances for 4:3 Aspect, in inches (feet)

Image Size in inches (feet)						MIN		MAX	
Diagonal		Width		Height		Throw		Throw	
60	(5.0)	48	(4.0)	32	(3.0)	89	(7.4)	113	(9.5)
72	(6.0)	57	(4.7)	43	(3.6)	107	(8.9)	136	(11.4)
84	(7.0)	67	(5.6)	50	(4.2)	124	(10.4)	159	(13.3)
100	(8.3)	80	(6.7)	60	(5.0)	148	(12.4)	189	(15.8)
120	(10.0)	96	(8.0)	72	(6.0)	178	(14.9)	227	(19.0)

Minimum distance to screen is 59 inches (4.9 feet)

Specifications

Brightness

Resolution

Mouse Control

Contrast

Image Element Type 0.7" DMD, DDR,

Digital Micromirror Device

DLP by Texas Instruments, XGA

1100 ANSI lumens

1024 x 768 pixels (H x V)

800:1

fh 15-100 kHz, fv 43.5-130 Hz Scanning Frequency

Manual zoom 1.3X

1:8 to 2.4:1 width to throw Lens Throw Ratio

distance

Keystone Correction Digital, +/- 15 degrees Aspect Ratio 4:3, 16:9, selectable SVGA, VGA, XGA, SXGA Computer Compatibility PC and Mac

NTSC, PAL, SECAM, SDTV Video Compatibility

(480i), EDTV (480p) Image Control Freeze function, electronic

magnification, pan and Picture-

in-Picture Using USB Front/rear

Projection Modes 24 bit (16.7 million) Color Reproduction

Lamp 120W UHP Lamp Life 3000 hours (typical) Audio 1 speaker, 1 watt Throw Distance 5 to 35 ft.

2.7 to 22.2 ft. Screen Size Inputs, Video (1) Min DIN 4-pin, s-video

(1) RCA, composite video Inputs, Computer (1) DVI, M1D/A, VESA with

USB mouse

(1) Audio, stereo mini jack Kensington lock slot Security Fan Level 32dB, ultra auiet

Operating Temperature 5 to 40 degrees C AC 100-240V, 50/60 Hz, Power

155 watt

7.8" x 2.5" x 6.1" Size (WxHxD)

Weight 2.4 lbs. Shipping Weight 10 lbs.

Safety

11.8" x 12.2" x 13.2" Carton Size

Accessories Included Remote control, batteries, power cord, RCA video cable, DVI cable with USB, audio cable (stereo mini), operator's manual and soft carrying case.

Optional Accessories

UL/CSA, FCC Class B Lamp 456-241; rolling briefcase; 185-406

DUKANE

Audio Visual Products 2900 Dukane Drive St. Charles, Illinois 60174 www.dukcorp.com/av



Toll-free: 800-676-2485 630-584-5156 Fax: avsales@dukcorp.com Two (2) year limited warranty

Peace-of-Mind Loaner Program.

on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 12 month